Nomograph for

the Prediction of Minimum Semi-Fluidization Velocity of Irregular Particles in Gas-Solid Systems

-G. K. Roy*

T HE author has earlier (3) given two nomographs tor the direct prediction of minimum and maximum semi-fluidization velocity for gas-solid systems. The nomographs have been prepared on the basis of the correlations developed by the author (C²). In a recent communication Roy and Sen Gupta (⁴) have given a correlation which relates the ratio of the minimum semi-fluidization to the minimum fluidization velocity with the system parameters. The correlation is—

$$\frac{G_{osf}}{G_{mf}} = 2.66 \times 10^{2} \left(\frac{D_{c}}{d_{p}}\right)^{0.62} \left(\frac{Q_{s}}{Q_{f}}\right)^{-1} (R)^{0.5}$$

The onset of fluidization velocity can be calculated from Leva's generalized equation (1).

$$G_{mf} = \frac{0.005 \ g_{c} \cdot Q_{f} \left(Q_{s} - Q_{f}\right) d_{p}^{2} \phi_{s}^{2}}{M} \cdot \frac{\epsilon_{pa}^{3}}{(1 - \epsilon_{pa})}$$


With the help of equation (1), a nomograph has been prepared (fig. 1) for the rapid estimation of the minimum semi-fludization velocity ratio and with the help of minimum fluidization velocity, obtained from equation (2), the actual value of the minimum semi-fluidization velocity can be calculated.

Accuracy of the nomograph:—

The value obtained from nomograph, has been compared with the respective values obtained by the other two methods, viz., from the equation and the actual experiment. The percentage deviations have also been calculated.

Example:—

| System: | Table salt-air. | |
|---------------------|-----------------------------|-------------------------|
| Diameter of column | (D_c) | 0.045 m. |
| Particle size | (d _p) (4.14.14. | 0.000442 m. |
| Particle density | (P _s) | 2100 kg./m [*] |
| Fluid density | (ℓ_f) | 1.2 kg/m ³ |
| Fluid Viscosity | (μ) ₁ | 0.00018 poise. |
| Bed expansion ratio | (R) | 3.0 |
| Fixed bed porosity | (ε_{da}) | 0.588 |
| Sphericity | (φs) | 0.452 |



Calculate and compare the values of minimum semifluidization velocity for the above case.

Solution:

(i) From equation—

$$\frac{G_{osf}}{G_{mf}} = 2.66 \times 10^{2} \left(\frac{D_{c}}{d_{p}}\right)^{0.62} \left(\frac{\ell_{s}}{\ell_{f}}\right)^{-1} (R)^{0.5}$$

$$D_{c}/d_{p} = 101.8$$

$$\frac{\ell_{s}}{\ell_{f}} = 1750$$

$$R = 3.0$$

$$\frac{Gosf}{Gmf} = 2.66 (10)^{2} (101.8)^{0.62} (1750)^{-1} (3)^{0.5}$$

$$= 4.63$$

*The author is teaching at the Dept. of Chemical Engineering, Regional Engg. College, Rourkela-8 (Orissa.)

| Table 1 | | | | |
|-------------|----|-----------|---------|--|
| —Comparison | of | G_{osf} | values— | |

| ^G osf | Gosf Kg./hr. m ² | | Percentage deviation of nomograph values. | | |
|------------------|-----------------------------|-------------|---|-------------------------|--|
| Nomograph | Experiment | Calculation | From experimental value | From caluculated value. | |
| 2260 | 2275 | 2275 | -0.66 | -0.66 | |

$$G_{mf} = 0.005 (9.81)(3100)^{2}(0.000442)^{2}(1.2)$$

$$\times (2100 - 1.2)(0.452)^{2}(0.588)^{3}$$

$$\div (0.00018) 10(3600)(1-0.588)$$

$$= 491 \text{ Kg lhr. m}^{2}$$

$$G_{osf} = 491 \text{ Kg. |hr. m}^{3}$$

$$= 4.63 \text{ x } 491$$

$$= 2275 \text{ Kg|hr. m}^{3}$$

(ii) From experiment—

$$G_{osf} = 2275 \text{ Kg.}|\text{hr. m}^2$$

(iii) From nomograph—

$$\frac{G_{osf}}{G_{mf}}$$
 = 4.60
 G_{osf} = 4.60 x 491
= 2260 Kg.|hr. m^a

Conclusion

It is observed that the value of minimum semi-fluidization velocity compare favourably well with those calculated by the equation and also with the experimental values. The deviations have been found to be almost negligible.

Acknowledgement

The author acknowledges the encouragements of Dr. P. Sen Gupta, Assistant Professor, Chemical Engineering, I.T.I., Kharagpur.

D_c = Inside diameter of column (or semifluidizer), Nomenclature L,

d_p = Particle diameter, L

 $g_c = Gravitational constant, L <math>\theta^{-2}$.

 G_{mf} = Minimum semi-fluidization velocity, $ML^{-2}\theta^{-1}$

h = Height of semi-fluidized bed, L.

h_s = Height of initial static bed, L.

R = Bed expansion ratio in semi-fluidization, dimensionless, h/h_s .

Greek letters

 g s = Density of solid, ML⁻³

^gf = Density of fluid, ML-3

 μ = Viscosity of fluid, $ML^{-1}\theta^{-1}$

 ϕ_s = Sphericity of solid.

 ϵ_{pa} = Porosity of packed bed.

REFERENCES

- **1.** Leva, M. "Fluidization", Mc Graw Hill Book Co. Inc., (1959).
- 2. Roy, G. K. and Sen Gupta, P., Paper accepted for publication in the British Chem, Engg.
- 3. Roy, G. K. and Sen Gupta, P., Paper communicated to the British Chem. Engg., for publication.
- 4. Roy, G. K. and Sen Gupta, P., Paper communicated to the 'Indian Journal of Technology' for publication.

Improve your productivity — Subscribe to

INDUSTRIAL TRAINING

—A quarterly journal devoted to development and training of human resources in industry.

Annual Subscription: Rs. 20.00

Write to:

INDUSTRIAL PUBLICATIONS

210, Dr. D. N. Road, Bombay 400 001.